



Typ
TS-CZ1520

Technische Daten

Typ:	4-polig
Länge:	38mm
Durchmesser:	29mm
Wellendurchmesser:	4mm/3,17mm
Gewicht:	105g

Typ	[Kv]	[Ri]	Max V	Max A	Max Power(W)
TS-CZ1520 *5	8300	3,50	10,00	120,00	650
TS-CZ1520 *6	6900	4,70	12,00	110,00	650
TS-CZ1520 *7	5900	6,50	14,00	100,00	650
TS-CZ1520 *8	5200	8,00	16,00	85,00	650
TS-CZ1520 *9	4600	9,7	18,00	70,00	650
TS-CZ1520 *10	4140	12,00	20,00	65,00	650
TS-CZ1520 *11	3760	14,00	22,00	60,00	650
TS-CZ1520 *12	3450	17,00	25,00	55,00	650
TS-CZ1520 *13	3180	19,20	27,00	50,00	650
TS-CZ1520 *14	2950	23,00	28,00	45,00	650
TS-CZ1520 *15	2760	26,50	30,00	45,00	650
TS-CZ1520 *16	2580	28,00	32,00	40,00	650
TS-CZ1520 *17	2430	33,20	35,00	38,00	650
TS-CZ1520 *18	2300	35,00	37,00	35,00	650
TS-CZ1520 *19	2180	42,00	40,00	32,00	650
TS-CZ1520 *20	2070	44,30	42,00	30,00	650

www.tenshock-motors.de



Erfolge

2009 Bulgaria Mini Eco 1er Platz

Besonders geeignet für Mini Eco