



Typ
TS-CZ1530

Technische Daten

| | |
|--------------------|------------|
| Typ: | 4-polig |
| Länge: | 48mm |
| Durchmesser: | 29mm |
| Wellendurchmesser: | 4mm/3,17mm |
| Gewicht: | 140g |

| Typ | [Kv] | [Ri] | Max V | Max A | Max Power(W) |
|--------------|------|--------|-------|-------|--------------|
| TS-CZ1530*5 | 5500 | 0,0035 | 13 | 120 | 1000 |
| TS-CZ1530*6 | 4600 | 0,005 | 15 | 110 | 1000 |
| TS-CZ1530*7 | 3950 | 0,0072 | 18 | 100 | 1000 |
| TS-CZ1530*8 | 3450 | 0,0088 | 21 | 85 | 1000 |
| TS-CZ1530*9 | 3100 | 0,0113 | 23 | 70 | 1000 |
| TS-CZ1530*10 | 2750 | 0,014 | 23 | 65 | 1000 |
| TS-CZ1530*11 | 2500 | 0,0165 | 28 | 60 | 1000 |
| TS-CZ1530*12 | 2300 | 0,0198 | 31 | 55 | 1000 |
| TS-CZ1530*13 | 2150 | 0,0235 | 34 | 50 | 1000 |
| TS-CZ1530*14 | 2000 | 0,0255 | 36 | 45 | 1000 |
| TS-CZ1530*15 | 1850 | 0,029 | 39 | 45 | 1000 |

www.tenshock-motors.de

Erfolge

2009 June Pilzen ECO-EXP 1st Place TS-CZ1530/5T

Besonders geeignet für ECO & Hydro