



Typ
TS-CZ2240

Technische Daten

Typ:	6-polig
Länge:	60mm
Durchmesser:	38mm
Wellendurchmesser:	5mm
Gewicht:	280g

Typ	[Kv]	[Ri]	Max V	Max A	Max Power(W)
TS-CZ2240 *5	3100	4,20	17,50	140	2200
TS-CZ2240 *6	2560	5,80	21,00	120	2200
TS-CZ2240 *7	2200	7,80	24,50	100	2200
TS-CZ2240 *8	1900	9,90	28,00	88	2200
TS-CZ2240 *9	1700	12,00	31,50	80	2200
TS-CZ2240 *10	1530	14,50	35,00	72	2200
TS-CZ2240 *11	1400	17,90	38,50	64	2200
TS-CZ2240 *12	1280	20,70	42,00	60	2200
TS-CZ2240 *13	1180	25,50	45,50	52	2200
TS-CZ2240 *14	1100	29,50	49,00	48	2200
TS-CZ2240 *15	1020	31,80	52,50	46	2200
TS-CZ2240 *16	960	36,00	56,00	44	2200
TS-CZ2240 *17	900	42,00	60,00	40	2200
TS-CZ2240 *18	860	44,00	63,00	38	2200
TS-CZ2240 *19	810	52,00	67,00	36	2200
TS-CZ2240 *20	770	54,00	70,00	34	2200
TS-CZ2240 *21	730	64,00	74,00	32	2200
TS-CZ2240 *22	700	67,00	77,00	30	2200

Erfolge

2009 Germany International Mono II 1st Place

Besonders geeignet für Mono 2&3